

INDOOR ACCESS POINT ENCLOSURE KIT

Part No: PSKX600S



For Cisco Aironet 1600, 2600, 2700, 3500, 3600 & 3700 Series Access



This access point enclosure kit is designed specifically for the range of Cisco Aironet Wi-Fi access points. Its unique modular design supports up to a total of 6 external RP-TNC bulkhead antenna ports. It is hence compatible with the following Cisco access point models and the complete range of Cisco Wi-Fi antennas.



BENEFITS

The enclosure enables Cisco access points to be deployed into a variety of harsh environments to protect your investment by preventing damage to the access point from water and dust.

A pressure compensation device is fitted as standard enabling the access points to be installed in environments that are prone to condensation issues such as cold stores and blast chillers.

Another key benefit is the unique design whereby the access point antenna ports are replicated externally. This is most important as it enables rapid deployment of your chosen Cisco antennas outside the enclosure thus maximising the range and performance of the antennas.

PLEASE CONTACT DW WIFI TO REQUEST INFORMATION ON OUR FULL RANGE OF ACCESSORY PRODUCTS FOR THE CURRENT RANGE OF CISCO ACCESS POINTS AND PATCH ANTENNAS

HOW CAN WE HELP YOU?

DW WiFi Hermes House, Andoversford Link, Andoversford Business Park, Andoversford, Gloucestershire, GL54 4LB Tel: +44 (0)1242 820693 sales@dw-wifi.com www.wifiprofessionalservices.com

INDOOR ACCESS POINT ENCLOSURE KIT

Part No: PSKX600S



For Cisco Aironet 1600, 2600, 2700, 3500, 3600 & 3700 Series Access



The polystyrene enclosure kit ships with a back plate for mounting the access point using its bracket. This secures to the inside of the enclosure via 6 screws.


The enclosure lid seals against a gasket located on the enclosure box and is attached using 6 polycarbonate lid fixing screws.

Each enclosure comes pre-fitted with an Ethernet cable gland through which the Ethernet data cable can be routed inside the enclosure for connection to the access point whilst maintaining the IP rating of the enclosure.



Fluctuations in the ambient temperature can cause pressure conditions that can lead to condensation into the enclosure. Each enclosure is hence fitted with a PCD pressure compensation device to help equalise the pressure.

The generic design provided for a total of 6 removable blanking plugs. This can be removed as required for fitting the required number of antenna ports for your access point in the form of custom made Antenna Pigtail Cables.



The antenna pigtail cables are available to order separately. These are fitted with a RP-TNC bulkhead antenna port one end for fitting in place of the blanking plugs. The other end is fitted with a right angle RP-TNC connector for attachment to the antenna ports located on the front face of the Cisco access point. The antenna cable is low loss to minimise signal loss.

Enclosure Dimensions

Height:	360 mm
Width:	254 mm
Depth (including lid):	111 mm

Enclosure Characteristics

Ingress Protection Rating:	IP54 (IP66 if self amalgamating tape used to seal antenna connections)
Ambient Temperature (Min):	Minus 35 Degrees Centigrade
Ambient Temperature (Max):	80 Degrees Centigrade
Ambient Temperature (24 h):	60 Degrees Centigrade
Max. Rel. Humidity at 40 degrees C:	50%
Rated insulation voltage AC:	690V
Protection Class:	II- isolate protection acc. VDE 0106 Protective insulation
Halogen-Free:	YES
Heavy Metals Free:	YES
PVC Free:	YES
Silicone Free:	YES
UV Resistance:	NO (Indoor Use Only)
Weatherproof:	NO (Indoor Use Only)
Combustion Behaviour to UL:	5VA nach UL 50/ UL 646C

HOW CAN WE HELP YOU?

DW WiFi Hermes House, Andoversford Link, Andoversford Business Park, Andoversford, Gloucestershire, GL54 4LB Tel: +44 (0)1242 820693 sales@dw-wifi.com www.wifiprofessionalservices.com